

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Per Beming, <i>et al.</i>	§	Group Art Unit:	2462
Application No.	10/595,312	§	Examiner:	Duong, Christine
Filed:	04/06/2006	§	Confirmation No:	7185
Attorney Docket No:	P17894-US1	§		
Customer No.:	27045	§		

For: Coordinated Data Flow Control and Buffer Sharing in UMTS

Via EFS-Web


Mail Stop Appeal Brief - Patents
Commissioner for Patents
P. O. Box 1450
Alexandria, VA 22313.1450

CERTIFICATE OF TRANSMISSION BY EFS-WEB

Date of Transmission: June 1, 2010

I hereby certify that this paper or fee is being transmitted to the United States Patent and Trademark Office electronically via EFS-Web.

Type or Print Name: Jennifer Hardin



AMENDED APPEAL BRIEF SUBMITTED UNDER 35 U.S.C. §134

This Appeal Brief is submitted to appeal the decision of the Primary Examiner, set forth in a Final Official Action dated October 19, 2009, finally rejecting claims 13-17, and the Advisory Action dated January 12, 2010; the brief has been amended in response to the Notification of Non-Compliant Appeal Brief issued on April 29, 2010.

The Commissioner is hereby authorized to charge any appropriate fees under 37 C.F.R. §41.20(b)(2) that may be required by this paper, and to credit any overpayment, to Deposit Account No. 50-1379.

Real Party in Interest

The real party in interest, by assignment, is: Telefonaktiebolaget LM Ericsson (publ)
SE-164 83
Stockholm, Sweden

Related Appeals and Interferences

None.

Status of Claims

Claims 1-12 and 18 were previously cancelled and are not appealed; claims 13-17 remain pending in the application. Claims 13 and 14 stand rejected, under 35 U.S.C. §103(a), as being unpatentable over what the Examiner has deemed as Applicant's Admitted Prior Art" ("APA") in view of Calvignac (U.S. Patent No. 5,784,698) and Miyoshi, *et al.* (U.S. Patent Publication No. 2003/0087662 A1); and, claims 15-17 stand rejected, under 35 U.S.C. §103(a), as being unpatentable over APA in view of only Miyoshi.

Status of Amendments

The claims set out in the Claims Appendix include all entered amendments. No amendment has been filed subsequent to the final rejection.

Summary of Claimed Subject Matter

Claim Element	Specification Reference
13. A control method for regulating the flow of data between a first transmitting radio network node and a second transmitting radio network node in a radio transmission network, comprising the steps of:	Page 18, line 21, <i>et seq.</i>
said second transmitting radio network node receiving data from said first transmitting radio network node to be forwarded to plural user entities via an air interface; wherein: the first transmitting radio network node sends a capacity request to the second transmitting radio network node requesting the second transmitting radio network node for permission to send an indicated number of data units that are pending in the first transmitting radio network node; and, the second transmitting radio network node, in response to the capacity request, sends an allocation frame to the first transmitting radio	Figure 12, Step 90 Figure 12, Step 92 Figure 12, Step 120

network node, said allocation frame indicating the number of data units the first transmitting radio network node is given permission to transmit, this latter number being referred to as credits;	
wherein the second transmitting radio network node, if buffer resources for storing of data units at the second transmitting radio network node are limited for each data flow between the first and second transmitting radio network nodes, performs the steps of:	Figure 11, Step 82; Page 18, lines 21-22
counting the instantaneous number of requested data units in each data flow to obtain a total number of requested data units;	Figure 13, Step 131
computing the total number of credits to be granted in each data flow by subtracting from a target buffer filling level for the total number of data flows the total number of data units currently stored in each of the buffers and the total number of credits previously given but not yet received; and,	Figure 14, Step 140
distributing the total number of credits proportionally to radio channel qualities indicated by said user entities.	Figure 12, Step 120

Claim Element	Specification Reference
15. A control method for regulating the flow of data between a first transmitting radio network node and a second transmitting radio network node in a radio transmission network, comprising the steps of:	Page 18, line 21, <i>et seq.</i>
said second transmitting radio network node receiving data from said first transmitting radio network node to be forwarded to plural user entities via an air interface, wherein:	Figure 12, line 14, <i>et seq.</i>
the first transmitting radio network node sends a capacity request to the second transmitting radio network node requesting the second transmitting radio network node for permission to send an indicated number of data units that are pending in the first transmitting radio network node; and,	Figure 12, Step 92
the second transmitting radio network node, in response to the capacity request, sends an allocation	Figure 12, Step 120

frame to the first transmitting radio network node, said allocation frame indicating the number of data units the first transmitting radio network node is given permission to transmit, this latter number being referred to as credits; and,	
distributing the number of credits given by the second transmitting radio network node proportionally to radio channel qualities indicated by said user entities to which the second transmitting radio network node is scheduling radio transmission of data units.	Figures 13 and 14 Page 20, line 7, <i>et seq.</i>

Claim Element	Specification Reference
16. A radio network node for regulating the flow of data from a transmitting node, comprising:	Figure 5; Page 9, line 1, <i>et seq.</i>
a buffering resource;	Figure 5, elements 9 Page 9, line 6
a capacity allocation device for allocating individual amounts of user data to individual user entities;	Page 9, line 2, <i>et seq.</i> Figure 5, element 23
a flow control protocol and a scheduler;	Figure 5, element 16 Page 9, line 5
wherein the capacity allocation device comprises a counter for keeping a running count of the instantaneous number of outstanding credits, outstanding credits being defined as the number of data units that the allocation device has permitted the transmitting node to send, although the corresponding number of data units has not yet arrived at the radio network node;	Figure 5, elements 29 Page 9, line 15
a distribution device adapted to distribute the total number of credits given by the radio network node proportionally to radio channel qualities indicated by said user entities to which the scheduler is scheduling radio transmission of data units.	Page 12, line 23, <i>et seq.</i>

The specification references listed above are provided solely to comply with the USPTO's current regulations regarding appeal briefs. The use of such references should not be interpreted to limit the scope of the claims to such references, nor to limit the scope of the claimed invention in any manner.

Grounds of Rejection to be Reviewed on Appeal

- 1.) Whether claims 13 and 14 are unpatentable over what the Examiner has deemed as Applicant's Admitted Prior Art" ("APA") in view of Calvignac (U.S. Patent No. 5,784,698) and Miyoshi, *et al.* (U.S. Patent Publication No. 2003/0087662 A1); and,
- 2.) Whether claims 15-17 are being unpatentable over APA in view of Miyoshi.

Arguments

- 1.) **Claims 13 and 14 are patentable over Applicant's Admitted Prior Art" ("APA") in view of Calvignac and Miyoshi**

Claim 13 recites:

13. A control method for regulating the flow of data between a first transmitting radio network node and a second transmitting radio network node in a radio transmission network, comprising the steps of:

said second transmitting radio network node receiving data from said first transmitting radio network node to be forwarded to plural user entities via an air interface; wherein:

the first transmitting radio network node sends a capacity request to the second transmitting radio network node requesting the second transmitting radio network node for permission to send an indicated number of data units that are pending in the first transmitting radio network node; and,

the second transmitting radio network node, in response to the capacity request, sends an allocation frame to the first transmitting radio network node, said allocation frame indicating the number of data units the first transmitting radio network node is given permission to transmit, this latter number being referred to as credits;

wherein the second transmitting radio network node, if buffer resources for storing of data units at the second transmitting radio network node are limited for each data flow between the first and second transmitting radio network nodes, performs the steps of:

counting the instantaneous number of requested data units in each data flow to obtain a total number of requested data units;

computing the total number of credits to be granted in each data flow by subtracting from a target buffer filling level for the total number of data flows the total number of data units currently stored in each of the buffers and the total number of credits previously given but not yet received; and,

distributing the total number of credits proportionally to radio channel qualities indicated by said user entities. (emphasis added)

As noted in response to the Non-Final Office Action dated April 2, 2009, the control method for regulating the flow of data between first and second transmitting radio network nodes recited in independent claim 13 (as well as independent claims 15 and 16) is characterized, in part, by distributing the total number of transmission credits to be granted to the user entities proportionally to the radio channel qualities indicated by the user entities. For claim 13 (as well as claims 15 and 16), the Examiner acknowledged that Applicant's Admitted Prior Art (APA) and Calvignac do not disclose distributing a total number of credits (for transmission of data units) proportionally to radio channel qualities indicated by the user entities. (Office Action dated April 2, 2009; Page 10, lines 1-4, and page 12, lines 4-7) To overcome that deficiency in the prior art, the Examiner looks to the teachings of Miyoshi, stating that Miyoshi discloses: "HDDR is a communication method whereby a base station performs scheduling for allocating communication resources to communication terminals by time division, and also sets a transmission rate for each communication terminal according to the downlink channel quality," referring to paragraph [0003] thereof. The Applicants believe the Examiner reads too much into the teachings of Miyoshi. As those skilled in the art will recognize, setting the transmission rate for each communication terminal according to the downlink channel quality experienced by each such terminal does not limit the transmission rate that can be set for other terminals; *i.e.*, the transmission rate set for one communication terminal according to HDR does not limit the transmission rate that can be set for another communication terminal. *In contrast*, the control method recited in claim 13 (as well as claims 15 and 16) is directed to managing the limited capacity of a radio network node (*e.g.*, due to limited buffer resources) which are apportioned proportionally to radio channel qualities indicated by user entities to which data units will be transmitted; *i.e.*, granting more transmission credits to one entity reduces, proportionally, the number that can be granted to another entity.

In the Final Office Action dated October 19, 2009, the Examiner maintained the rejection of claims 13 and 14 as being unpatentable over APA in view of Calvignac and Miyoshi; and, claims 15-17 as being unpatentable over APA in view of Miyoshi. In responding to Applicants' arguments submitted in response to the prior office action, the Examiner stated, exactly as asserted in the prior office action, that:

"Miyoshi discloses 'HDR is a communication method whereby a base station performs scheduling for allocating communication resources to communication terminals by time division, and also sets a transmission rate for each communication terminal according to the downlink channel quality'."

As noted in Applicants' prior arguments to distinguish that asserted teaching of Miyoshi, the Applicants believe the Examiner reads too much into the teachings thereof. As those skilled in the art will recognize, setting the transmission rate for each communication terminal according to the downlink channel quality experienced by each such terminal does not limit the transmission rate that can be set for other terminals; i.e., the transmission rate set for one communication terminal according to HDR does not limit the transmission rate that can be set for another communication terminal. In the final office action, the Examiner attacked that distinction by stating that:

"Based on the DRC signal transmitted from each communication terminal, the base station sets a transmission rate for each communication terminal, and sends a signal to each communication terminal via a control channel indicating communication resource allocation to each communication terminal (Miyoshi [0006]). This shows that data is sent proportionally to channel quality for each terminal. Therefore, Miyoshi discloses distributing the total number of credits proportionally to radio channel qualities indicated by said user entities." (emphasis added)

Again, the Examiner reads too much into the teachings of Miyoshi. Although Miyoshi describes setting a transmission rate by a base station based on a DRC signal transmitted by different communication terminals, it does not follow that Miyoshi discloses "distributing [a] total number of credits proportionally to radio channel qualities indicated by said user entities;" to conclude otherwise is to not read the credit mechanism of Applicants' invention in the context of the claim as a whole.

As previously noted by the Applicants, the control methods for regulating the flow of data between first and second transmitting radio network nodes recited in

independent claim 13 (and claims 15 and 16) is characterized, in part, by distributing the total number of transmission credits to be granted to the user entities proportionally to the radio channel qualities indicated by the user entities. For claim 13 (as well as claims 15 and 16), the Examiner has previously acknowledged that Applicant's Admitted Prior Art (APA) and Calvignac do not disclose distributing a total number of credits (for transmission of data units) proportionally to radio channel qualities indicated by the user entities. As those skilled in the art will recognize, setting the transmission rate for each communication terminal according to the downlink channel quality experienced by each such terminal does not limit the transmission rate that can be set for other terminals; *i.e.*, the transmission rate set for one communication terminal according to HDR does not limit the transmission rate that can be set for another communication terminal. *In contrast*, the control method recited in claim 13 (as well as claims 15 and 16) is directed to managing the limited capacity of a radio network node (*e.g.*, due to limited buffer resources) which are apportioned *proportionally to radio channel qualities indicated by user entities* to which data units will be transmitted; *i.e.*, granting more transmission credits to one entity reduces, proportionally, the number that can be granted to another entity.

In responding to that technical distinction in the final office action, the Examiner asserted that "the features upon which the applicant relies . . . are not recited in the rejected claim(s)." The Applicants disagree. Claim 13 concludes with the limitation of: "distributing the total number of credits proportionally to radio channel qualities indicated by said user entities." (emphasis added). As those skilled in the art will recognize, if there are a "total" number of credits, and they are distributed "proportionally," then granting more transmission credits to one entity will, necessarily, reduce the number that can be granted to another entity. The Examiner has not pointed to any such teaching in Miyoshi and, accordingly, claim 13 (as well as claims 15 and 16) is not obvious over APA, Calvignac and Miyoshi. Furthermore, whereas claim 14 is dependent from claim 13, and includes the limitations thereof, it is also not obvious in view of APA, Calvignac and Miyoshi.


2.) **Claims 15-17 are patentable over APA in view of Miyoshi**

Independent claims 15 and 16, as noted *supra*, recite limitations analogous to those of claim 13 and, thus, they are also distinguishable over APA and the teachings of Calvignac and Miyoshi. Therefore, the Examiner has also not established a *prima facie* case of obviousness for claims 15 and 16. Furthermore, whereas claim 17 is dependent from claim 16, and includes the limitations thereof, it is also not obvious.

CONCLUSION

The claims currently pending in the application are patentable over the cited references and, therefore, the Applicants request that the Examiner's claim rejections be reversed and the application be remanded for further prosecution.

Respectfully submitted,



Roger S. Burleigh
Registration No. 40,542
Ericsson Patent Counsel

Date: June 1, 2010

Ericsson Inc.
6300 Legacy Drive, M/S EVR1 C-11
Plano, Texas 75024

(972) 583-5799
roger.burleigh@ericsson.com

CLAIMS APPENDIX

1-12. (Cancelled)

13. (Previously Presented) A control method for regulating the flow of data between a first transmitting radio network node and a second transmitting radio network node in a radio transmission network, comprising the steps of:

said second transmitting radio network node receiving data from said first transmitting radio network node to be forwarded to plural user entities via an air interface; wherein:

the first transmitting radio network node sends a capacity request to the second transmitting radio network node requesting the second transmitting radio network node for permission to send an indicated number of data units that are pending in the first transmitting radio network node; and,

the second transmitting radio network node, in response to the capacity request, sends an allocation frame to the first transmitting radio network node, said allocation frame indicating the number of data units the first transmitting radio network node is given permission to transmit, this latter number being referred to as credits;

wherein the second transmitting radio network node, if buffer resources for storing of data units at the second transmitting radio network node are limited for each data flow between the first and second transmitting radio network nodes, performs the steps of:

counting the instantaneous number of requested data units in each data flow to obtain a total number of requested data units;

computing the total number of credits to be granted in each data flow by subtracting from a target buffer filling level for the total number of data flows the total number of data units currently stored in each of the buffers and the total number of credits previously given but not yet received; and,

distributing the total number of credits proportionally to radio channel qualities indicated by said user entities.

14. (Previously Presented) The control method recited in claim 13, further comprising the step of limiting the total sum of user data in all data streams to a desired value less than or equal to the total requested number of data units.

15. (Previously Presented) A control method for regulating the flow of data between a first transmitting radio network node and a second transmitting radio network node in a radio transmission network, comprising the steps of:

said second transmitting radio network node receiving data from said first transmitting radio network node to be forwarded to plural user entities via an air interface, wherein:

the first transmitting radio network node sends a capacity request to the second transmitting radio network node requesting the second transmitting radio network node for permission to send an indicated number of data units that are pending in the first transmitting radio network node; and,

the second transmitting radio network node, in response to the capacity request, sends an allocation frame to the first transmitting radio network node, said allocation frame indicating the number of data units the first transmitting radio network node is given permission to transmit, this latter number being referred to as credits; and,

distributing the number of credits given by the second transmitting radio network node proportionally to radio channel qualities indicated by said user entities to which the second transmitting radio network node is scheduling radio transmission of data units.

16. (Previously Presented) A radio network node for regulating the flow of data from a transmitting node, comprising:

a buffering resource;

a capacity allocation device for allocating individual amounts of user data to individual user entities;

a flow control protocol and a scheduler;

wherein the capacity allocation device comprises a counter for keeping a running count of the instantaneous number of outstanding credits, outstanding credits being

defined as the number of data units that the allocation device has permitted the transmitting node to send, although the corresponding number of data units has not yet arrived at the radio network node;

a distribution device adapted to distribute the total number of credits given by the radio network node proportionally to radio channel qualities indicated by said user entities to which the scheduler is scheduling radio transmission of data units.

17. (Previously Presented) The radio network node recited in claim 16, wherein the capacity allocation device comprises a counter for keeping a running count of user data pending in the transmitting node.

18. (Cancelled)

* * *

EVIDENCE APPENDIX

None.

RELATED PROCEEDINGS APPENDIX

None.